

EL12M

12" POWERED STAGE MONITOR



Overview

The EL12M is the first dedicated powered stage monitor from Yorkville Sound.

It delivers 1200 watts of peak power (600 watts program) through a 12" speaker and 1" high-frequency driver in a stage-ready enclosure that weighs less than 40 pounds.

Its two selectable monitor modes are voiced for vocals, and its flat mode is ideal for instrument sources like synthesizers, electronic drum kits, or for use as an FRFR solution for amp modelers. It also features an XLR / 1/4" input jack, two XLR outputs, and powerCON® TRUE1 compatible input and output connectors, so it integrates easily into any PA system.

Features

- 1200 W Peak Power (600 W Program)
- 12" Coaxial Woofer with 2.5" Voice Coil
- 1" HF Driver with 1.75" Voice Coil
- 3 Voicing Modes
- Onboard Limiter
- Combi-Jack XLR / 1/4" Input and 2 XLR Outputs
- powerCON® TRUE1 Compatible Input and Output
- 15 mm Birch Plywood Construction
- Made in Canada



Specifications

Power Rating	1200 W Peak 600 W Program
Max SPL	132 dB Peak (120 dB Continuous)
Frequency Response	60 Hz - 20 kHz (+/- 3 dB)
Crossover Frequency	1500 Hz
LF Woofer	12" Coaxial Woofer with 2.5" Voice Coil
HF Driver(s)	1" HF Driver with 1.75" Voice Coil
HF Dispersion (H x V)	60° x 60°
Level Controls	Yes
EQ Controls	Mon 1, Mon 2, and Flat Modes
Inputs	1x XLR / TRS
Outputs	2x XLR
Flypoints	No
Bar Handles	2x Side, 1x Bottom
Pole Mount Adapter	No
Enclosure Materials	15 mm Birch Plywood
Cabinet Finish	Textured Paint
Grille	Powder-Coated Steel
Power Cable	powerCON® TRUE1 compatible connectors (Input / Output)
Power Consumption (Typ / Max)	2.5A, 6A
Dimensions (DWH)	17" x 16.3" x 12.2" 43.2 cm x 33.8 cm x 31 cm
Weight	38.7 lbs / 17.6 kg

Specifications subject to change without notice

